

PRODUCT GUIDE

V-SERIES

— Standard Specifications 50Hz

Spec Model	Capacity		Surface	Ventilator	Air Flow	Dimensions (mm)		Connections (mm)		Weight
	kW	kcal/h	m ²	Ø x kW x N x EA	CMM	L x W x H	L' x W'	IN	OUT	kg
SYC-V003	8.51	3 HP	25	500 x 0.2 x 6 x 1	64	777 x 760 x 925	670 x 300	19.05	12.7	80
SYC-V005	14.18	5 HP	36	600 x 0.4 x 6 x 1	120	917 x 860 x 1,026	810 x 350	22.22	15.88	90
SYC-V008	21.27	16,859	58	500 x 0.2 x 6 x 2	128	1,337 x 860 x 1,026	1,230 x 350	22.22	19.05	120
SYC-V010	28.37	24,368	75	600 x 0.4 x 6 x 2	240	1,577 x 890 x 1,075	1,470 x 350	28.58	19.05	150
SYC-V015	42.56	36,458	120	600 x 0.4 x 6 x 2	240	1,577 x 930 x 1,130	1,470 x 350	34.92	22.22	180
SYC-V020	56.74	47,554	146	630 x 0.75 x 6 x 2	288	1,877 x 1,028 x 1,130	1,770 x 460	34.92	28.58	240
SYC-V025	70.93	60,331	191	630 x 0.75 x 6 x 3	360	2,397 x 1,028 x 1,130	2,290 x 460	41.28	28.58	300
SYC-V030	85.12	79,318	261	630 x 0.75 x 6 x 3	432	2,747 x 1,028 x 1,130	2,640 x 460	41.28	28.58	380
SYC-V040	113.60	94,045	296	600 x 0.4 x 6 x 4	480	2,176 x 1,790 x 1,331	1,840 x 1,140	53.98	28.58	500
SYC-V050	141.84	126,541	410	600 x 0.4 x 6 x 6	720	2,926 x 1,790 x 1,331	2,590 x 1,140	53.98	28.58	560
SYC-V060	157.76	136,272	441	700 x 0.75 x 6 x 6	864	3,124 x 1,903 x 1,328	2,791 x 1,251	53.98	34.92	650

